



JYM 1SN

Code	ID(inch)	OD(mm)	W.P(Bar)	B.P(Bar)	Max.Length(M)
JYM1SN001	3/16	11.5	250	1000	100
JYM1SN002	1/4	12.7	225	900	100
JYM1SN003	5/16	14.4	215	860	100
JYM1SN004	3/8	16.5	180	720	100
JYM1SN005	1/2	19.5	160	640	100
JYM1SN006	5/8	23	130	520	100
JYM1SN007	3/4	26.7	105	420	100
JYM1SN008	1	34.5	87	350	100
JYM1SN009	1 1/4	42.2	63	250	40
JYM1SN010	1 1/2	48.9	50	200	40
JYM1SN011	2	61.9	40	160	40

EN853 1SN/SAE 100 R1AT

Tube: Oil resistant synthetic rubber

Reinforcement: One high tensile steel wire braid

Cover: Abrasion and weather resistant synthetic rubber

Temperature range: from -40°C to +100°C

SAE100R1AT/1SN

内胶层: 耐油合成橡胶

增强层: 一层高强度钢丝编织

外胶层: 耐腐蚀, 耐气候的合成橡胶

温度范围: 40°C 至+100°C

JINYUAN RUBBER MANUFACTURING LTD

E-mail: sales@goflexrubber.com

